

Construction Material Guidelines

Inert Recyclables (10 yd lowboy bins)	Construction and Demolition Recyclables (25 and 40 yd bins)	Trash
<p>Clean Asphalt</p> <p>Clean Concrete (2ft x2ft max)</p> <p>Clean stucco</p> <p>Concrete block and brick</p> <p>Clean loads of River Rock</p>	<p>Clean untreated wood</p> <p>Clean drywall</p> <p>Metal</p> <p>Porcelain Tile</p> <p>Porcelain sinks and bath tubs</p> <p>Ceramic Tile</p> <p>Cardboard</p> <p>Types 1 and 2 Plastics</p> <p>Ceiling Tile</p> <p>Green Waste (chipper size)</p>	<p>Painted/treated wood</p> <p>Concrete loads with rebar exposed and more than 10% dirt or rock.</p> <p>Stucco loads with paper and wire mesh</p> <p>Dirt</p> <p>Insulation</p> <p>Plastic packaging materials</p> <p>Styrofoam</p> <p>Vinyl Flooring</p> <p>Carpet and Carpet Pad</p> <p>Red brick</p> <p>Industrial Plastics</p> <p>Palm Fronds</p> <p>Succlulents</p>

Mixed Construction and Demolition debris loads (Demo Loads) can contain some trash but not more than 30% of a full container can be items listed in the trash column or the load will be rejected.